


MAXIMUM JACKET O.D. ACCEPTED BY EXTERNAL STRAIN RELIEF = 8 DIA (0.315")  
 MAXIMUM JACKET O.D. ACCEPTED BY INTERNAL STRAIN RELIEF = 8 DIA (0.315")  
 MAXIMUM CONDUCTOR SIZE ACCEPTED BY TERMINALS = 2.5 (14 AWG)

**CORDAGE PREPARATION**

CONDUCTOR INSULATION COLOR	CONDUCTOR COLOR CODE	"LENGTH"	"STRIP"
GREEN/YELLOW	GROUND	15	6
BLUE	NEUTRAL	25	6
BROWN	LINE	25	6





**CONFIGURATIONS**



ALL DIMENSIONS ARE IN MILLIMETERS

CORDAGE PREPARATION



**SPECIFICATIONS**

TEMPERATURE RATING	100°C (212°F) Continuous Use, 200°C (392°F) Intermittent Use
CURRENT RATING	10 AMPERE
VOLTAGE RATING	250 VOLT AC
CONTACTS	2 POLE 3 WIRE GROUNDING
MATERIALS	- PORCELAIN TERMINAL BASE - PLASTIC COVER
REMARKS	STRAIGHT STYLE BODY
NOTE	SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

TITLE			
ROUND PIN BAND HEATER CONNECTOR (ERGE)			
STRAIGHT TYPE			
SCALE	DATE	PART NO.	REV
NONE	12-28-2009	111-10111	-